



**1**

**PRODUCT AND COMPANY IDENTIFICATION**

**Product Identifier:** Alpha Style 6445-2-BRN  
**Common Name:** Coated Fiberglass  
**SDS Number:** 0357  
**Revision Date:** 2/7/2018

**Supplier Details:** Alpha Engineered Composites LLC.  
145 Lehigh Avenue  
Lakewood, NJ 08701

**Contact:** James Palmer  
**Phone:** 732-634-5700  
**Fax:** 732-634-1430  
**Email:** [jpalmer@alphainc.com](mailto:jpalmer@alphainc.com)  
**Internet:** [www.alphainc.com](http://www.alphainc.com)

**Classification of Substance****GHS Classification in Accordance with 29 CFR 1910 (OSHA HCS):**

Health, Skin corrosion/irritation, 3  
 Health, Specific target organ toxicity - Single exposure, 3

**GHS Label Elements, Including Precautionary Statements**

**GHS Signal Word:** **WARNING**

**GHS Hazard Pictograms:**

**GHS Hazard Statements:**

H316 - Causes mild skin irritation  
 H335 - May cause respiratory irritation

**GHS Precautionary Statements:**

P264 - Wash \_ thoroughly after handling.

**Hazards not Otherwise Classified (HNOC) or not Covered by GHS**

**Route of Entry:** This material may enter the body through inhalation of nuisance dust.  
**Target Organs:** Respiratory System  
**Inhalation:** Sore, raspy throat  
**Skin Contact:** Redness and possible rash; itching  
**Eye Contact:** Itching and redness  
**Ingestion:** N/A

Chemical Ingredients		
CAS#	%	Chemical Name
65997-17-3		Fibrous Glass
1309-64-4		Antimony oxide (Sb203)
0		Compounded Acrylic Coating

Fibrous Glass (CAS 65997-17-3)

Exposure Limits: OSHA PEL 15 mg/m<sup>3</sup> (total), 5 mg/m<sup>3</sup> (respirable). ACGIH TLV 1 f/cc

**Inhalation:** Remove person to fresh air. If condition persists, seek medical attention.  
**Skin Contact:** Rinse with copious quantities of cool water. If rash or itching persists, seek medical attention.  
**Eye Contact:** Rinse with water. Do not rub eyes. Seek medical attention.  
**Ingestion:** Not applicable.

Flash Point (Method Used): >250 C by TOC      Flammable Limits

LEL: N/A      UEL: N/A

Extinguishing Media: Water, carbon dioxide, or dry chemical

Special Fire Fighting Procedures: Thermal decomposition of fiber coating may produce an irritating mixture of smoke and fumes.

Unusual Fire and Explosion Hazards: None

Material is a solid in roll form. If accidentally released, rewind material back onto roll.

**Handling Precautions:** Use adequate material handling equipment.

**Storage Requirements:** Store in dry place. Use may be at temperature extremes based on product data, but storage should be at ambient temperature.

**Engineering Controls:** Local exhaust; dust collection

**Personal Protective Equipment:** HMIS PP, A | Safety Glasses

Safety glasses; cotton gloves; long sleeve clothing

Wash thoroughly with soap and water after handling

**Appearance:** Red Coated Fabric

**Physical State:** Solid

**Specific Gravity or Density:** 1.22

**Boiling Point:** N/A

**Vapor Pressure:** N/A

**Potential Hydrogenii:** N/A

**Odor:** No Odor

**Solubility:** Negligible

**Freezing or Melting Point:** > 1000 F

**Vapor Density:** N/A

**Chemical Stability:** Material is stable.

**Conditions to Avoid Identification:** None known.

**Materials to Avoid Identification:** Strong oxidizing agents.

**Hazardous Decomposition:** Carbon monoxide; carbon dioxide; hydrogen chloride

**Hazardous Polymerization:** Will Not Occur.

Direct contact with fiberglass materials or exposure to airborne fiberglass dust may irritate the skin, eyes, nose and throat. Fiberglass can cause itching due to mechanical irritation from the fibers. This is not an allergic reaction to the material. Breathing fibers may irritate the airways resulting in coughing and a scratchy throat. Some people are sensitive to the fibers, while others are not.

No known hazards except for airborne fibers caused by nuisance dust. 10 milligrams per cubic meter for fiber diameters less than 7 microns.

Incineration preferred in a federal, state, or local approved facility.

None special required.

Component (CAS#) [%] - CODES

-----  
Fibrous Glass (65997-17-3) [n/a%] TSCA

Antimony oxide (Sb2O3) (1309-64-4) [n/a%] CERCLA, CSWHS, EPCRAWPC, MASS, PA, PROP65, TSCA, TXAIR

Compounded Acrylic Coating (0) [n/a%]


Regulatory CODE Descriptions

-----  
TSCA = Toxic Substances Control Act  
CERCLA = Superfund clean up substance  
CSWHS = Clean Water Act Hazardous substances  
EPCRAWPC = EPCRA Water Priority Chemicals  
MASS = MA Massachusetts Hazardous Substances List  
PA = PA Right-To-Know List of Hazardous Substances  
PROP65 = CA Prop 65  
TXAIR = TX Air Contaminants with Health Effects Screening Level


**NFPA:** Health = 1, Fire = 0, Reactivity = 0, Specific Hazard = n/a

**HMIS III:** Health = 1, Fire = 0, Physical Hazard = 0

**HMIS PPE:** A - Safety Glasses



HMIS	
HEALTH	1
FLAMMABILITY	0
PHYSICAL HAZARD	0
PERSONAL PROTECTION	A



**Disclaimer:**

Although reasonable care has been taken in the preparation of this document, we extend no warranties and make no representations as to the accuracy or completeness of the information contained herein, and assume no responsibility regarding the suitability of this information for the user's intended purposes or for the consequences of its use. Each individual should make a determination as to the suitability of the information for their particular purpose(s).