



GHS Safety Data Sheet

Alpha Engineered Composites

Alpha Style 84215/9480 BH PS

PRODUCT AND COMPANY IDENTIFICATION

Product Identifier: Alpha Style 84215/9480 BH PS **Common Name:** Foil/ Fiberglass Laminate

SDS Number: 0906 **Revision Date:** 2/8/2018

Supplier Details: Alpha Engineered Composites LLC.

145 Lehigh Avenue Lakewood, NJ 08701

 Contact:
 James Palmer

 Phone:
 732-634-5700

 Fax:
 732-634-1430

Email: jpalmer@alphainc.com **Internet:** www.alphainc.com

SDS Number: 0906 Page: 1/5 Revision Date: 2/8/2018

Classification of Substance

GHS Classification in Accordance with 29 CFR 1910 (OSHA HCS):

Health, Respiratory or skin sensitization, 1 Skin

GHS Label Elements, Including Precautionary Statements

GHS Signal Word: WARNING GHS Hazard Pictograms:



GHS Hazard Statements:

H317 - May cause an allergic skin reaction

GHS Precautionary Statements:

P264 - Wash _ thoroughly after handling.

Hazards not Otherwise Classified (HNOC) or not Covered by GHS

Route of Entry: This material may enter the body through inhalation of nuisance dust.

Target Organs:Respiratory SystemInhalation:Sore, raspy throat

Skin Contact: Redness and possible rash; itching

Eye Contact: Itching and redness

Ingestion: N/A

3

COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Ingredients		
CAS#	%	Chemical Name
65997-17-3		Fibrous Glass
7429-90-5	14.6-	Aluminum Foil
	15.0%	
67700-43-0	4.6-5.0%	Urethane Adhesive
9003-01-4	16-18.5%	Acrylic Adhesive
63394-02-5		Silicone Coated Paper

Fibrous Glass (CAS 65997-17-3)

Exposure Limits: OSHA PEL 15 mg/m3 (total), 5 mg/m3 (respirable). ACGIH TLV 1 f/cc (60-66%)

4 FIRST AID MEASURES

Inhalation: Remove person to fresh air. If condition persists, seek medical attention.

Skin Contact: Rinse with copious quantities of cool water. If rash or itching persists, seek medical attention.

Eye Contact: Rinse with water. Do not rub eyes. Seek medical attention.

Ingestion: Not applicable.

SDS Number: 0906 Page: 2 / 5 Revision Date: 2/8/2018

FIRE FIGHTING MEASURES

Flash Point (Method Used): >250 C by TOC Flammable Limits

LEL: N/A UEL: N/A

Extinguishing Media: Water, carbon dioxide, or dry chemical

Special Fire Fighting Procedures: Thermal decomposiiton of fiber coating may produce an irritating mixture of smoke and

fumes.

5

Unusual Fire and Explosion Hazards: None

ACCIDENTAL RELEASE MEASURES 6

Material is a solid in roll form. If accidently released, rewind material back onto roll.

HANDLING AND STORAGE

Handling Precautions: Use adequate material handling equipment.

Storage Requirements: Store in dry place. Use may be at temperature extremes based on product data, but storage should be

at ambient temperature.

EXPOSURE CONTROLS/PERSONAL PROTECTION 8

Engineering Controls: Local exhaust: dust collection

Personal Protective HMIS PP. B | Safety Glasses, Gloves

Equipment: Safety glasses; cotton gloves; long sleeve clothing

Wash thoroughly with soap and water after handling

PHYSICAL AND CHEMICAL PROPERTIES 9

Appearance: Aluminized Fabric Tape

Physical State: Solid Odor: No Odor Specific Gravity or 2.2 Solubility: Negligible

Density: **Boiling Point:**

N/A **Freezing or Melting** > 500 F Point:

Vapor Pressure: N/A Vapor Density: N/A

Potentia Hydrogenii: N/A

10 STABILITY AND REACTIVITY

Chemical Stability: Material is stable. **Conditions to** None known

Avoldentification:

Materials to Avoldentification: Strong oxidizing agents.

Hazardous Decomposition: Carbon monoxide; carbon dioxide; nitrogen oxide; cyanide

Hazardous Polymerization: Will Not Occur.

TOXICOLOGICAL INFORMATION 11

Direct contact with fiberglass materials or exposure to airborne fiberglass dust may irritate the skin, eyes, nose and throat. Fiberglass can cause itching due to mechanical irritation from the fibers. This is not an allergic reaction to the material. Breathing fibers may irritate the airways resulting in coughing and a scratchy throat. Some people are sensitive to the fibers, while others are not.

SDS Number: 0906 Page: 3/5 Revision Date: 2/8/2018

12 ECOLOGICAL INFORMATION

No known hazards except for airborne fibers caused by nuisance dust. 10 milligrams per cubic meter for fiber diameters less than 7 microns.

13 DISPOSAL CONSIDERATIONS

Incineration perferred in a federal, state, or local approved facility.

14 TRANSPORT INFORMATION

None special required.

15 REGULATORY INFORMATION

Component (CAS#) [%] - CODES

Fibrous Glass (65997-17-3) [n/a%] TSCA

Aluminum Foil (7429-90-5) [14.6-15.0%] EPCRAWPC, MASS, NJHS, OSHAWAC, PA, SARA313, TSCA, TXAIR

Urethane Adhesive (67700-43-0) [4.6-5.0%] TSCA

Acrylic Adhesive (9003-01-4) [16-18.5%] TSCA

Silicone Coated Paper (63394-02-5) [n/a%]

Regulatory CODE Descriptions

TSCA = Toxic Substances Control Act
EPCRAWPC = EPCRA Water Priority Chemicals
MASS = MA Massachusetts Hazardous Substances List
NJHS = NJ Right-to-Know Hazardous Substances
OSHAWAC = OSHA Workplace Air Contaminants
PA = PA Right-To-Know List of Hazardous Substances
SARA313 = SARA 313 Title III Toxic Chemicals
TXAIR = TX Air Contaminants with Health Effects Screening Level


NFPA: Health = 1, Fire = 0, Reactivity = 0, Specific Hazard = n/a

HMIS III: Health = 1, Fire = 0, Physical Hazard = 0

HMIS PPE: B - Safety Glasses, Gloves







Disclaimer:

Although reasonable care has been taken in the preparation of this document, we extend no warranties and make no representations as to the accuracy or completeness of the information contained herein, and assume no responsibility regarding the suitability of this information for the user's intended purposes or for the consequences of its use. Each individual should make a determination as to the suitability of the information for their particular purpose(s).