



Alpha Engineered Composites

Alpha Style PPSA-44/PS

SDS

1	PRODUCT AND COMPANY IDENTIFICATION
Product Identifier: Common Name: SDS Number: Revision Date:	Alpha Style PPSA-44/PS Foil/ Scrim/ Film Laminate 0487 2/9/2018
Supplier Details:	Alpha Engineered Composites LLC. 145 Lehigh Avenue Lakewood, NJ 08701
Contact: Phone: Fax: Email: Internet:	James Palmer 732-634-5700 732-634-1430 jpalmer@alphainc.com www.alphainc.com

Classification of Substance

GHS Classification in Accordance with 29 CFR 1910 (OSHA HCS):

Health, Skin corrosion/irritation, 3 Health, Specific target organ toxicity - Single exposure, 3

GHS Label Elements, Including Precautionary Statements

GHS Signal Word: WARNING

GHS Hazard Pictograms:



GHS Hazard Statements:

H316 - Causes mild skin irritation

H335 - May cause respiratory irritation

GHS Precautionary Statements:

P264 - Wash _ thoroughly after handling.

Hazards not Otherwise Classified (HNOC) or not Covered by GHS

Route of Entry:	This material may enter the body through inhalation of nuisance dust.
Target Organs:	Respiratory system
Inhalation:	Sore, raspy throat
Skin Contact:	Redness and possible rash; itching
Eye Contact:	Itching and redness
Ingestion:	N/A
3	COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Ingredients		
CAS#	%	Chemical Name
65997-17-3		Fibrous Glass
1309-64-4		Antimony oxide (Sb2O3)
0		Aluminum Foil
0		Polypropylene Film
0		Urethane Adhesive
0		Acrylic Adhesive
0		Silicone Coated Paper

Fibrous Glass (CAS 65997-17-3) Exposure Limits: OSHA PEL 15 mg/m3 (total), 5 mg/m3 (respirable). ACGIH TLV 1 f/cc

4 FIRST AID MEASURES

Inhalation:	Remove person to fresh air. If condition persists, seek medical attention.
Skin Contact:	Rinse with copious quantities of cool water. If rash or itching persists, seek medical attention.
Eye Contact:	Rinse with water. Do not rub eyes. Seek medical attention.
Ingestion:	Not applicable.

2

6

Flash Point (Method Used): >250 C by TOC Flammable Limits

LEL: N/A UEL: N/A

Extinguishing Media: Water, carbon dioxide, or dry chemical

Special Fire Fighting Procedures: Thermal decomposiiton of fiber coating may produce an irritating mixture of smoke and fumes.

Unusual Fire and Explosion Hazards: None

ACCIDENTAL RELEASE MEASURES

Material is a solid in roll form. If accidently released, rewind material back onto roll.

7	HANDLING AND STORAGE	
Handling Precautions: Storage Requirements:		
8	EXPOSURE CONTROLS/PERSONAL PROTECTION	
Engineering Controls: Personal Protective Equipment:	Local exhaust; dust collection Safety glasses; cotton gloves; long sleeve clothing	

Wash thoroughly with soap and water after handling

9	PHYSICAL AND CHEMICAL PROPERTIES			
Appearance:	White Face Has Pressure Sensitive Adhesive with Release Paper/Silver Back			
Physical State:	Solid	Odor:	No odor	
Specific Gravity or Density:	1.8	Solubility:	Negligible	
Boiling Point:	N/A	Freezing or Melting Point:	> 350 F	
Vapor Pressure:	N/A	Vapor Density:	N/A	
Potentia Hydrogenii:	N/A			

STABILITY AND REACTIVITY

Chemical Stability: Conditions to Avoldentification:	Material is stable. None known.
Materials to Avoldentification: Hazardous Decomposition: Hazardous Polymerization:	Strong oxidizing agents. Carbon monoxide; carbon dioxide; nitrogen oxide; cyanide; hydrogen bromide Will Not Occur.

11

10

TOXICOLOGICAL INFORMATION

Direct contact with fiberglass materials or exposure to airborne fiberglass dust may irritate the skin, eyes, nose and throat. Fiberglass can cause itching due to mechanical irritation from the fibers. This is not an allergic reaction to the material. Breathing fibers may irritate the airways resulting in coughing and a scratchy throat. Some people are sensitive to the fibers, while others are not. No known hazards except for airborne fibers caused by nuisance dust. 10 milligrams per cubic meter for fiber diameters less than 7 microns.

13 DISPOSAL CONSIDERATIONS

Incineration perferred in a federal, state, or local approved facility.

14

15

TRANSPORT INFORMATION

None special required.

REGULATORY INFORMATION

Component (CAS#) [%] - CODES

Fibrous Glass (65997-17-3) [n/a%] TSCA

Antimony oxide (Sb2O3) (1309-64-4) [n/a%] CERCLA, CSWHS, EPCRAWPC, MASS, PA, PROP65, TSCA, TXAIR

Aluminum Foil (0) [n/a%]

Polypropylene Film (0) [n/a%]

Urethane Adhesive (0) [n/a%]

Acrylic Adhesive (0) [n/a%]


Silicone Coated Paper (0) [n/a%]

Regulatory CODE Descriptions

TSCA = Toxic Substances Control Act CERCLA = Superfund clean up substance CSWHS = Clean Water Act Hazardous substances EPCRAWPC = EPCRA Water Priority Chemicals MASS = MA Massachusetts Hazardous Substances List PA = PA Right-To-Know List of Hazardous Substances PROP65 = CA Prop 65 TXAIR = TX Air Contaminants with Health Effects Screening Level

OTHER INFORMATION

NFPA:Health = 1, Fire = 0, Reactivity = 0, Specific Hazard = NoneHMIS III:Health = 1(Chronic), Fire = 0, Physical Hazard = 0HMIS PPE:B - Safety Glasses, Gloves



Disclaimer:

Although reasonable care has been taken in the preparation of this document, we extend no warranties and make no representations as to the accuracy or completeness of the information contained herein, and assume no responsibility regarding the suitability of this information for the user's intended purposes or for the consequences of its use. Each individual should make a determination as to the suitability of the information for their particular purpose(s).

16